

NAME

<code>archive_write_set_format,</code>	<code>archive_write_set_format_7zip,</code>
<code>archive_write_set_format_ar,</code>	<code>archive_write_set_format_ar_bsd,</code>
<code>archive_write_set_format_ar_svr4,</code>	<code>archive_write_set_format_by_name,</code>
<code>archive_write_set_format_cpio,</code>	<code>archive_write_set_format_cpio_newc,</code>
<code>archive_write_set_format_filter_by_ext,</code>	
<code>archive_write_set_format_filter_by_ext_def,</code>	
<code>archive_write_set_format_gnutar,</code>	<code>archive_write_set_format_iso9660,</code>
<code>archive_write_set_format_mtree,</code>	<code>archive_write_set_format_mtree_classic,</code>
<code>archive_write_set_format_mtree_default,</code>	<code>archive_write_set_format_pax,</code>
<code>archive_write_set_format_pax_restricted,</code>	<code>archive_write_set_format_raw,</code>
<code>archive_write_set_format_shar,</code>	<code>archive_write_set_format_shar_dump,</code>
<code>archive_write_set_format_ustar,</code>	<code>archive_write_set_format_v7tar,</code>
<code>archive_write_set_format_warc,</code>	<code>archive_write_set_format_xar,</code>
<code>archive_write_set_format_zip,</code>	— functions for creating archives

LIBRARY

Streaming Archive Library (libarchive, -larchive)

SYNOPSIS

```
#include <archive.h>

int
archive_write_set_format(struct archive *, int code);

int
archive_write_set_format_7zip(struct archive *);

int
archive_write_set_format_ar(struct archive *);

int
archive_write_set_format_ar_bsd(struct archive *);

int
archive_write_set_format_ar_svr4(struct archive *);

int
archive_write_set_format_by_name(struct archive *, const char *name);

int
archive_write_set_format_cpio(struct archive *);

int
archive_write_set_format_cpio_newc(struct archive *);

int
archive_write_set_format_filter_by_ext(struct archive *,
    const char *filename);

int
archive_write_set_format_filter_by_ext_def(struct archive *,
    const char *filename, const char *def_ext);

int
archive_write_set_format_gnutar(struct archive *);
```

```

int
archive_write_set_format_iso9660(struct archive *);

int
archive_write_set_format_mtree(struct archive *);

int
archive_write_set_format_pax(struct archive *);

int
archive_write_set_format_pax_restricted(struct archive *);

int
archive_write_set_format_raw(struct archive *);

int
archive_write_set_format_shar(struct archive *);

int
archive_write_set_format_shar_dump(struct archive *);

int
archive_write_set_format_ustar(struct archive *);

int
archive_write_set_format_v7tar(struct archive *);

int
archive_write_set_format_warc(struct archive *);

int
archive_write_set_format_xar(struct archive *);

int
archive_write_set_format_zip(struct archive *);

```

DESCRIPTION

These functions set the format that will be used for the archive.

The library can write a variety of common archive formats.

archive_write_set_format()

Sets the format based on the format code (see `archive.h` for the full list of format codes). In particular, this can be used in conjunction with **archive_format()** to create a new archive with the same format as an existing archive.

archive_write_set_format_by_name()

Sets the corresponding format based on the common name.

archive_write_set_format_filter_by_ext(),

archive_write_set_format_filter_by_ext_def()

Sets both filters and format based on the output filename. Supported extensions: .7z, .zip, .jar, .cpio, .iso, .a, .ar, .tar, .tgz, .tar.gz, .tar.bz2, .tar.xz

archive_write_set_format_7zip()

archive_write_set_format_ar_bsd(),

archive_write_set_format_ar_svr4(),

archive_write_set_format_cpio()

archive_write_set_format_cpio_newc()

archive_write_set_format_gnutar()

archive_write_set_format_iso9660()

archive_write_set_format_mtree()

```
archive_write_set_format_mtree_classic()
archive_write_set_format_pax()
archive_write_set_format_pax_restricted()
archive_write_set_format_raw()          archive_write_set_format_shar()
archive_write_set_format_shar_dump()
archive_write_set_format_ustar()        archive_write_set_format_v7tar()
archive_write_set_format_warc()         archive_write_set_format_xar()
archive_write_set_format_zip()
Set the format as specified. More details on the formats supported by libarchive can be found in
the libarchive-formats(5) manual page.
```

RETURN VALUES

These functions return **ARCHIVE_OK** on success, or **ARCHIVE_FATAL**.

ERRORS

Detailed error codes and textual descriptions are available from the **archive_errno()** and **archive_error_string()** functions.

SEE ALSO

tar(1), libarchive(3), archive_write(3), archive_write_set_options(3), cpio(5),
libarchive-formats(5), mtree(5), tar(5)